



Bee3 PLUS All-in-one live video production

The most reliable, all-in-one video production system that's equipped with a 10.1-inch touch screen, two HDMI inputs and one HDMI output locally. Bee3 PLUS supports to Record, stream, and switch up to 2 HD inputs simultaneously and take your video production to the next



KEY FEATURES



10.1" Touchscreen
Confidence monitoring, switching, recording, and streaming



Stream to views everywhere
Simultaneously live stream to YouTube, Facebook or web browsers locally over rtsp, rtmp streaming protocol.



Video inputs
Connect your camera or video source with HDMI inputs



Audio support
Use the 3.5mm inputs, or line-level inputs. Built-in attenuation and gain adjustment mean you get perfect sound fidelity



1080p HD recordings
Hardware-accelerated box provides flawless H.264 encoding for maximum performance.



Switch video sources live
Incredibly easy to use, new touchscreen makes switching between your connected sources or layouts a breeze. Or use the web to do switching



Local video output
Send your content to a larger confidence monitor through the local HDMI video output. Configure to share any input source or switched program output



Removable storage
USB for speedy transfer of files



Optional Hard disk inside
Upgrade local storage to 1T hard disk flexibly



Integrate into the 3rd central control system flexibly



Video input	2 x HDMI	
Audio input	Line in and mic in, hdmi audio	
Video output	1x HDMI for video output	
Video encoding	Codec	H.264
	Bitrate	1 to 30 Mb/s
	Resolution:	User selectable up to 1920 × 1080
Video switching	During live streaming and recording via the touch screen or web UI	
Video layout	PIP, POP, Single video	
Encoded programs	2 simultaneous 1080p programs at 30 fps (with up to 2 Full HD sources)	
Audio encoding	AAC (sampling @ 48 kHz)	
Network	1 ×1000 Ethernet port (RJ45)	
Storage	Hard disk	128G (optional selection of 1T capacity)
	USB 3.0	Automatic or manual copy via 1 USB 3.0 ports
Network Storage	FTP	
Recording formats	Mp4	
Control	Web panel, 10.1' touch screen, RS232 APIs	
Dimensions (W x D x H)	256 x 175 x 37 (mm)	
Power Consumption	30W	

REACH