



## MediaBoost HDMI-70TP & MediaBoost DVI-70TP

### HDMI/DVI CAT Extender

Remotely transmit full high resolution HDMI/DVI signals via category cable from up to 70/100 m with NUVOLA's new MediaBoost HDMI-70/100 TP while only using a single power source from either the transmitting or receiving end.

## Features

- Supports resolution up to 4K2K
- Transmitting distance up to 70/100 m
- Support RS232 and IR signals transmission
- Only single power supply is required at either transmitter or receiver end

## Specifications

Model	MediaBoost HDMI-70TP	
Description	HDMI CAT Transmitter	HDMI CAT Receiver
Input	1 x HDMI, 1 x RS232 (Phoenix), 1 x IR (3.5mm)	1 x RJ45 Network Port
Output	1 x RJ45 Network Port	1 x HDMI, 1 x RS232 (Phoenix), 1 x IR (3.5mm)
Signal Supported	HDMI, DVI, RS232, IR	
Resolution	800x600 --- 4096x2160	
Protocol	HDMI 1.4, DVI 1.0, HDCP, EDID	
Transmission Distance	70m (Also available for 100m)	
Size (WxDxH) in mm	102 x 70 x 25	
Weight	230g	
Input Voltage	5VDC 2A	
Operating Temperature	0°C - 50°C	
Storage Temperature	-25°C - 85°C	